

Bokhov Kin, I.M.

USSR/Corrosion. Protection from Corrosion.

J

Abs Jour: Ref Zhur-Khimiya, No 3, 1957, 10555

Author

Bokhovkin, I. M.
Arkhangelsk Forestry Institute Inst

: The Effect of Chromium and of Antimony on the Corrosion Title

of Wrought Iron

Orig Pub: Tr. Arkhang. lesotekhn. in-ta, 1955, Vol 16, 56-62

Abstract: Investigation of the corrosion (C) of graphitized and nongraphitized wrought iron alloyed with Cr and Sb in 1 N H₂SO₄ at 50° has shown that the graphitized specimens are subjected to greater C than the nongraphitized specimens. Maximum corrosive attack has been observed in iron-containing 0.42% Sb; the author explains this result by the chemical reaction between Cr and Sb. The opinion is expressed that in the absence of passivation the rate of C is determined by the inter-atomic bonds

in alloys.

Card 1/1

BOKHOUKIN, IM.

USSR/Corrosion - Protection from Corrosion, J

Abst Journal: Referat Zhur - Khimiya, No 19, 1956, 63826

Author: Bokhovkin, I. M.

Institution: None

Title: Effect of Cobalt on Corrosion of White Cast Iron

Original


Periodical: Tr. Arkhang. lesotekhn. in-ta, 1955, 16, 79-84

Abstract: Considered is the effect of Co on corrosion of white cast iron in

H₂SO₄. Noted is the difference in effect of Co on the rate of cor-

rosion of cast iron depending on the presence therein of Si.

Card 1/1



I. M. BakhovKIN

B-8

USSR/Thermodynamics - Thermochemistry. Equilibria.

Physical-Chemical Analysis. Phase Transitions.

Abs Jour

: Referat Zhur - Khimiya, No 6, 1957, 18536

Author

: Yu.I. Bokhovkina, I, 14. Bokhovkin.

Title

: Surface Tension in Binary Systems of Urea with Acetic

Acil and Its Chlor- Derivatives.

Orig Pub

: Zh. obshch. khimii, 1956, 26, No 4, 1062-1065

Abstract

: The measurement of the surface tension in binary systems of orea with acetic acid and its chlorderivatives monochloracetic, dichloracetic and trichloracetic acids was carried out by the method of greatest pressure in gas bubble in the temperature range of 45 to 900. It was shown that the isoterms of for the system wrea - acetic acid were convex towards the composition axis in consequence of the dissociation of the molecular compound CO(NH₂)₂.2CH₃COOH. A smooth rise of 3 without characteristical breaks together with

Card 1/2

- 214 -

Rokhov K. W. Im.

BOKHOVKIN, I.M.

Corrosion of alloys of the system zinc-antimony. Zhur.prikl.khim. 29 no.8:1298-1299 Ag '56. (MIRA 10:10)

1.Arkhangel'skiy lesotekhnicheskiy institut im. V.V. Kuybysheva.
(Corrosion and anticorrosives)
(Antimony--Zinc alloys)

BOKHOVKIN, I.M. USSR/Physical Chemistry. Thermodynamics, Thermochemistry, B-8 Equilibria, Physical-Chemical Analysis, Phase Transitions.

Ref Zhur-Khimiya, No 5, 1957, 14710. Abs Jour:

Author : I. M. Bokhovkin, Yu. I. Bokhovkina


Physical-Chemical Analysis of Binary Systems Produced by Acetamide with Organic Acids. I. Density, Viscosity Inst : and Electrical Conductivity of System Acetamide-Acetic Title


Acid.


Zh. obshch. khimii, 1956, 26, No 5, 1315-1318 Orig Pub:


The density, viscosity and electrical conductivity of the system acetamide (I) - acetic acid (II) were measured at 20, 60 and 800. The density isotherms are represented Abstract: by curves with a slight convexity towards the composition axis. The viscosity isotherms, convex towards the composition axis, indicate the dissociation of the associated compound in the system. The isotherms of the electrical conductivity are characterized by a maximum, which some-


Card 1/2











CIA-RDP86-00513R000206020018-2 "APPROVED FOR RELEASE: 06/09/2000

AUTHORS:

Bokhovkin, I. M., Veselkova, Ye. G.

79-28-3-55/61

TITLE:

Physical and Chemical Analysis of Binary Systems Formed of Phenol With Acetic Acid and Its Derivatives (Fiziko-khimicheskiy analiz dvoynykh sistem, obrazovannykh fenolom s

uksusnoy kislotoy i yeye khlorproiz odnymi)

PERIODICAL:

Zhurnal Obshchey Khimii, 1958, Vol. 28, Nr 3, pp. 819-823

(USSR)

ABSTRACT:

As is known the entrance of chloring into the radical of acetic acid leads to the increase of acidity and consequently to an intensification of the chemical reaction with other components (references). The problem of the present work is the reaction of phenol with acetic acid and its chlorine derivatives in liquid phase. The corresponding method was described earlier (references 2-5). The initial products were purified: acetic acid by freezing, phenol, monochloro- and trichloro acetic acid by distillation. The concentrations were expressed in molar percents, the surface tension in dyn/cm, the viscosity in centi-Poise. The surface tension, viscosity and density were investigated for all systems at 50, 70 and 90° C. The physical and chemical investigation of the binary

Card 1/2

Physical and Chemical Analysis of Binary Systems Formed of 79-28 3-55/61 Phenol With Acetic Acid and Its Derivatives

systems consisting of phenol with acetic acid and its chlorine derivatives was carried out according to the methods of density, viscosity and of surface tension. The isothermal lines of density, viscosity and surface tension in systems consisting of acetic acid and monochloroacetic acid with phenol do not give any hints as to the presence of compounds in molten medium. The isothermal lires of viscosity and surface tansion in the system trichlorcacetic acid-phenol as fusion diagram indicate the presence of the compound C6H5OH . CC13COOH. From the comparison of the isothermal lines of surface tension, density and viscosity of all three investigated systems can be seen that the introduction of chlorine into the radical of acetic acid leads to an increase of the chemical reaction of phenol with acetic acid derivatives. There are 6 figures, 9 tables, and 10 references all of which are Soviet.

ASSOCIATION:

Arkhangel'skiv lesotechnicheskiy institut

(Arkhangel'sk Institute for Forestry Engineering)

SUBMITTED:

February 2, 1957

Card 2/2

....

AUTHOR:

Bokhovkin, I. M.

79-28-4-3/60

TITLE:

Physical Chemical Investigation of the Interaction of Acetone With Acetic Acid and Its Chlorine Derivatives (Fiziko-khimicheskoye issledovaniye vzaimodeystviya atsetona s uksusnoy kislotoy i yeye khlorproizvodnymi)

PERIODICAL:

Zhurnal Obshchey Khimii, 1958, Vol. 28, Nr 4,

pp. 862-867 (USSR)

ABSTRACT:

The author observed the interaction of acetone with acetic acid and its chlorine derivatives in order to check the correctness of the assumptions made earlier (Ref. 6). In the present paper the author described the investigations of three binary systems: acetone - acetic acid, acetone - monochloroacetic acid and acetone - trichloroacetic acid. (Ye. G. Veselkova participated in the experimental work). Density, viscosity and surface tension were studied. The method of the experiments of these systems was described earlier (Refs. 2,5.5). A compound 2CH_COOH.

Card 1/3

CH3COCH3 exists in the homogeneous melted medium in the

Physical Chemical Investigation of the Interaction of Acetone With Acetic Acid and Its Chlorine Derivatives

79-28-4-3/60

system acetone - acetic, and in the system acetone - tri=chloroacetic acid a compound of CCl₃COOH.CH₃COCH₃ exists. It may be assumed that two compounds are formed

CH2C1COOH.CH3COCH3 and 2CH2C1COOH.CH3COCH3

in the system acetone - monochloro= acetic acid. Interaction of the components in the system acetone - acetic acid and their chlorine derivatives in= tensifies according to the substitution of hydrogen in the acetic acid radical by chlorine. From the comparison of the isothermal lines of density, viscosity and surface tension in the systems consisting of carbamide, acetamide and ace= tone with acetic acid and their chlorine derivatives con= clusions were drawn on a certain similarity of chemical phenomena which take place within them in the presence of the hydrogen binding). The author gave a comparison of the stable compounds which form in the systems of carbamide-, acetamide-, and acetone - acetic acid and their chlorine derivatives. The most stable compounds in the homogeneous medium are the compounds of acetamide and acetic acid and their chlorine derivatives since acetamide has the highest dielectric constant.

Card 2/3

Physical Chemical Investigation of the Interaction 79-28-4-3/60 of Acetone With Acetic Acid and Its Chlorine Derivatives

There are 9 figures, 4 tables and 10 references, all of

which are Soviet.

ASSOCIATION: Arkhangel'skiy lesotekhnicheskiy institut (Arkhangel'sk

Institute for Forestry)

SUBMITTED: March 26, 1957

Card 3/3

AUTHOR:

Bokhovkin, I. M.

SOV/79-29-6-5/72

TITLE:

Physico-chemical Investigation of the Double System

Hydrazine-Acetic Acid (Fiziko-khimicheskoye issledovaniye

dvoynoy sistemy gidrazin-uksusnaya kislota)

PERIODICAL:

Zhurnal obshchey khimii, 1959, Vol 29, Nr 6, pp 1793-1797

(USSR)

ABSTRACT:

Comparatively few data are available in publications on the physico-chemical analysis of the double salts which are formed from hydrazine and organic acids (Ref 1), although these investigations are of practical and theoretical interest. The hydrazine is characterized by the internuclear distance d (NN) = 1.47 Å and by the considerable polarity with the dipole length 0.38 Å. It is readily soluble in water and has a high dielectric constant (53 at 23°). It can therefore be used as well-ionizing solvent for many inorganic and organic compounds. On solution of organic compounds in hydrazine their electrolytic dissociation must increase. The hydrogen ion, being a good agent for the complex formation, causes the formation of compounds from hydrazine and acids as is the case with the solution of

Card 1/3

organic acids in acetamide (Refs 2,3), the dielectric constant of which is 59.1. In the present paper density,

Physico-chemical Investigation of the Double System SOV/79-29-6-5/72 Hydrazine-Acetic Acid

viscosity, surface tension, and specific electric conductivity in the above-mentioned system were investigated at 70, 75, and 80°. The isotherms of all these properties indicate the presence of the compound N_2H_4 . CH_3COOH in the molten homogeneous medium. The figures give the maxima of the isotherms of density and viscosity. The isothermal lines of the surface tension are S-like. In the isotherms of the electric conductivity a sharp break can be seen which corresponds with the compound mentioned. The curves of the temperature coefficients of the electric conductivity and viscosity also confirm the presence of the compound mentioned in a component ratio of 1 : 1 (maximum conductivity and minimum viscosity). A formation scheme of the compounds of hydrazine with acetic acid is suggested on the basis of the hydrogen bond so that the structure of the above compound had to correspond with the formula

Card 2/3

"APPROVED FOR RELEASE: 06/09/2000

CIA-RDP86-00513R000206020018-2

Physico-chemical Investigation of the Double System SOV/79-29-6-5/72

There are 3 figures, 2 tables, and 10 Soviet references.

ASSOCIATION:

Arkhangel'skiy lesotekhnicheskiy institut (Arkhangel'sk

Institute of Forestry)

SUBMITTED:

May 29, 1958

Card 3/3

5 (4)

AUTHOR: Bokhovkin I ...

807/79-29-8-6/81

TITLE:

Physico-chemical Analysis of the Binary Systems Formed by Phenol With Carbamide, Acetamide, and Acetone

PERIODICAL:

Zhurnal obshchey khimii, 1959, Vol 29, Nr 8, pp 2485 - 2489

ABSTRACT:

It was of interest to the author to investigate the chemical nature of the above reactions. Acetamide and acetone may be considered to be a carbamide in which the amino groups are replaced successively by one and two methyl radicals. As is known, phenols and amides are characteristic of hydrogen bonds. It was therefore of interest to investigate in what degree the hydrogen bond appears between dissimilar molecules, especially between phenol and carbamide, acetamide, and acetone in melted state as illustrated by the diagram; "composition - property". This investigation is of practical importance since phenol and carbamide are used together in the industrial production of carbamide resins. Viscosity, density, and surface tension of the binary systems mentioned in the title were investigated.

Card 1/2

The presence of a compound in a melted, homogeneous medium in the phenol - acetamide and phenol - acetone systems was de-

Physico-chemical Analysis of the Binary Systems Formed SOV/79-29-8-6/81 by Phenol With Carbamide, Acetamide, and Acetone

termined from the isothermal lines of viscosity and density, yet not the presence of a compound in the phenol - carbamide system. The isothermal lines of surface tension did not indicate the presence of a compound in any of the three systems. It was ascertained that the stability of the three systems depends on the dielectric constant of the component which enters into reaction with phenol. The degree of stability of the compounds in solid phase as well as in a melted, homogeneous medium may be shown in the following order: Acetamide-phenol) acetone-phenol > phenol-carbamide. The compounds ascertained at the interface of two phases and in a homogeneous medium are in all probability of the hydrogen-bond type. There are 3 figures, 3 tables, and 11 references, 8 of which are Soviet.

ASSOCIATION: Arkhangel'skiy lesotekhnicheskiy institut (Arkhangel'sk Insti-

SUBMITTED:

June 20, 1958

Card 2/2

CHESNOKOV, V.F.; BOKHOVKIN, I.M.

Thermal analysis of the ternary system acetamide - acetic acid - phenylacetic acid. Zhur.ob.khim. 30 no.7:2124-2127 J1 '60. (MIRA 13:7)

Arkhangel'skiy lesotekhnicheskiy institut.
 (Acetamide) (Acetic acid)

Corrosion of cadmium-antimony alloys in hydrochloric and nitric acid. Zhur. prikl. khim.33 no.6:1418-1421 Je '60. (MIRA 13:8) (Cadmium-antimony alloys)

24.7040 1043, 1160, 1147 18 8300 1138 22000 \$/076/61/035/004/006/018 B106/B201

AUTHOR:

Bokhovkin, I.M.

TITLE:

Corrosion of alloys of cadmium with artimony in sulfuric acid

PERIODICAL: Zhurnal fizicheskoy khimii, v. 35, no. 4, 1961, 789 - 792

TEXT: A study has been made of the corrosion rate of cadmium-antimony alloys in sulfuric acid as a function of the acid concentration. Great importance is attached to this problem in the practice in connection with the use of these alloys as semiconductor materials. The alloys were prepared by a method described by the author carlier (Ref. 4: Zh. prikl. pared by a method described by the author carlier (Ref. 4: Zh. prikl. pared by a method described by the author carlier (Ref. 4: Zh. prikl. pared by a method described by the author carlier (Ref. 4: Zh. prikl. pared by a themselved a good high, 8-10 mm in diameter). The metallographic analysis showed a good high, 8-10 mm in diameter). The metallographic analysis showed a good homogeneity of the alloys and the absence of segregation. The specimens homogeneity of the alloys and the absence of segregation. The temperature were treated with sulfuric acid for 1-6 hours at 40°C. The temperature constancy was attained by a thermostat. The corrosion rate was determined from the weight decrease of the specimens and indicated as g/m²hour. The sulfuric acid concentrations ranged between 1 and 24 N. Table 1 presents sulfuric acid concentrations ranged between 1 and 24 N. Table 1 presents the results obtained. With rising concentration of the sulfuric acid (up to 11-13 N) the corrosion rate of alloys with < 50% antimony also rises, card 1/6

2 2000

B/076/61/035/004/006/018 B106/B201

Corrosion of alloys of ...

Card 2/6

passes through a maximum, and again decreases with a further rise of the sulfuric acid concentration (18-24 N). The corrosion rate of the specimen with 52% antimony dropped little, but steadily, with a rise of acid concentration. The rate at which specimens with higher antimony contents were attacked was considerably slower, the corrosion rate slowly decreasing with a rise of sulfuric acid concentration. The author also studied the effect of two inhibitors (furfurole, dioxan) upon the corrosion of cadmium-antimony alloys. These inhibitors were added to the sulfuric acid in an amount of 1%. In alloys with high corrosion rate (0-50% Sb), the inhibitors reduced the corrosion rate considerably. While dioxan reduced the corrosion rate to about half, it was possible to suppress the corrosion process almost completely by the addition of furfurole. The inhibitors had practically no effect upon the lew corrosion rate of specimens with higher antimony contents. The third chapter of the present paper deals with alloy corrosion as a function of composition, and with the chemical reaction between the alloy components. The results obtained are shown in the figure. With increasing antimony content in the alloy (up to 30%) the corrosion rate rises, and drops very abruptly with a further increase of the antimony content to 52%. Specimens with higher

22000

Corrosion of alloys of ...

S/076/61/035/004/006/018 B106/B201

antimony contents exhibit a low, almost constant corrosion rate. The reason for this shape of the curves is the formation of the CdSb compound (52% Sb), and the more positive electrode potential of antimony (normal potential $Cd/Cd^{2+} = -0.40$ v, normal potential $Sb/Sh^{3+} = 0.2$ v). The abrupt drop of the curves at 50% Sb may be regarded as the limit of corrosion stability of the alloys. In this composition, a multilayered protective coating of compound CdSb is formed on the alloy surface, so that the corrosive medium cannot penetrate into the alloy interior. The increase of corrosion rate in the range of 0-30% Sb is manifestly due to the cathode process being rendered easier by the presence of the more electropositive antimony. There are 1 figure, 3 tables, and 4 Soviet-bloc references.

ASSOCIATION:

Arkhangel'skiy lesotekhnicheskiy institut

(Arkhangel'sk Institute of Wood Technology)

SUBMITTED:

July 13, 1960

Card 3/6

22000


Corrosion of alloys of ...

S/076/61/035/004/006/018 B106/B201

Table 1	Ø	Состав сплава.		З Концентрация серной и іслоты, №							
	СПЛАВОВ	Cd	8b	1	2	4	8	11	13	18	24
	1 2 3 4 5 6 7 8 9 10 11 12 13 14	100 95 92,5 90 70 55 52 50 48 45 42 35 20	5 7,5 10 30 45 48 50 52 55 58 65 80	2,8 2,9 3,6 5,4 3,8 3,8 3,8 4 0,6 0,5 0,4	8.4 6.5 6.8 7.9 4.8 4.4 4.4 0.6 0.5 0.4	16.4 17.0 17.7 18.0 30.9 12.1 6.2 5.0 1.3 0.5 0.4 0.4	39,9 34,7 34,9 35,9 51,9 9,8 9,7 1,1 0,4 0,4 0,3	40,3 40,3 40,4 40,7 56,0 27,1 10,4 9,6 0,8 0,3 0,3 0,3	40,3 40,4 40,8 41,8 58,0 6,2 5,2 0,7 0,3 0,3	17,1 18,9 23,9 28,9 30,1 14,1 0,4 0,3 0,3 0,3 0,2	13,9 17,1 20,0 23,1 25,9 12,4 1,8 0,8 0,4 0,3 0,3 0,3

Legend to Table 1: Corrosion rate of cadmium-antinony alloys in sulfuric acid, g/m²hour; (1) no. of alloys; (2) composition of alloy, %; (3) sulfuric acid concentration, N.

Card 4/6



2'2000

Corrosion of alloys of ...

S/076/61/035/004/006/018 B106/B201


Legend to the figure: Curves of corrosion rate of cadmium-antimony alloys in sulfuric acid as a function of the composition; ordinate - corrosion rate, g/m²hour; 1 - H₂SO₄+1% furfurole; 2 - 1 N H₂SO₄; 3 - 2 N H₂SO₄; 4 - 4 N H₂SO₄; 5 - 8 N H₂SO₄.


Card 6/6

LUK'YANOV, Yu.I. (Viadimir); MAKSIMETS, I.I. (Ternopol!); BOKHOVKIN,
V.M. (Ryazan!)

Suggestions and advice. Fiz.v shkole 23 no.1:60 Ja-F '63.

(MIRA 16:4)





USSR/Thermodynamics - Thermochemistry. Equilibria.

B-8

Physical-Chemical Analysis. Phase Transitions.

Abs Jour

: Referat Zhur - Khimiya, No 6, 1957, 18536

the rise of urea content in binary systems with chlorderivatives points to the absence of any chemical interaction between the components of the system in the liquid phase.

Cerá 2/2

- 215 -

BOKHOVKINA

USSR/Physical Chemistry. Thermodynamics, Thermochemistry, B-8 Equilibria, Physical-Chemical Analysis, Phase Transitions.

Abs Jour: Ref Zhur-Khimiya, No 5, 1957, 14710.

Author: I. M. Bokhovkin, Yu. I. Bokhovkina

Title

Inst

: Physical-Chemical Analysis of Binary Systems Produced by Acetamide with Organic Acids. I. Density, Viscosity and Electrical Conductivity of System Acetamide-Acetic

Acid.

Orig Pub: Zh. obshch. khimii, 1956, 26, No 5, 1315-1318

Abstract: The density, viscosity and electrical conductivity of

the system acetamide (I) - acetic acid (II) were measured at 20, 60 and 80°. The density isotherms are represented by curves with a slight convexity towards the composition axis. The viscosity isotherms, convex towards the composition axis, indicate the dissociation of the associated compound in the system. The isotherms of the electrical conductivity are characterized by a maximum, which some-


Card 1/2


USSR/Physical Chemistry. Thermodynamics, Thermochemistry, B-8 Equilibria, Physical-Chemical Analysis. Phase Transitions.


Abs Jour: Ref Zhur-Khimiya, No 5, 1957, 14710


Abstract: what shifts towards I with the temperature rise; a small breaking point is observed on the electrical conductivity isotherm of 20°, it corresponds to the compound 1: 1. The chemical interaction is very weakly expressed in the system I - II.


Card 2/2











BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.; VITMAN, Ye.O.

Thermal analysis of the ternary system carbamide - acetic acid - trichloroacetic acid. Zhur.ob.khim. 32 no.8:2415-2418 Ag *62. (MIRA 15:9)

1. Arkhangel'skiy lesotekhmicheskiy institut. (Urea) (Acetic acid) (Thermal analysis)

BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.

Physicochemical analysis of the ternary system carbanide - phenol - trichloroacetic acid. Zhur.ob.khim. 33 no.6:1722-1726 Je '63. (MIRA 16:7)

1. Arkhangel'skiy lesotekhnicheskiy institut. (Urea) (Phenol) (Acetic acid)

BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.; VITMAN, Ye.O.

Physicochemical analysis of the ternary system phenol - acetamide - monochloroacetic acid. Zhur.ob.khim. 33 no.7:2087-2090 J1 '63. (MIRA 16'8)

1. Arkhangel'skiy lesotekhnicheskiy institut.
(Phenols) (Acetamide) (Acetic acid)

BOKHOVKINA, Yu.I.; BOKHOVKIN, I.M.; VITMAN, Ye.O.

Physicochemical study of the ternary system carbamide - monochloroacetic acid - trichloroacetic acid. Zhur. ob. khim. 34 no. 3:723-727 Mr 164.

Physicochemical analysis of the ternary system phenol - acetamide - trichloroacetic acid. Ibid.:727-7.31 (MIRA 17:6)

1. Arkhangel'skiy lesotekhnicheskiy institut.

BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.; VITMAN, Ye.O.

Physicochemical investigation of the ternary system carbamide - acetamide - acid. Thur. ob. khim. 3/ nc. 59 1363-1365 My 164.

Physicochemical investigation of the ternary system phenol-monochloroscetic acid - trichloroscetic acid. Ibid.:1369-1371

Physicochemical investigation of the ternary system phenolacetic acid - monochloroacetic acid. Ibid.:1372-1375
(MIRA 17:7)

1. Arkhangel'skiy lesotekhnicheskiy institut.

BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.; UYEMLYANINA, L.S.

Physicochemical investigation of the ternary system carbanide-acetamide - monochloroacetic acid. Zhur. ob. khim. 34 no. 5s 1366-1369 My '64. (MIRA 17:7)

1. Arkhangel'skiy lesotekhnicheskiy institut.

BOKHOVKIN, I.M.; BOKHOVKINA, Yu.I.; VITMAN, Ye.O.

Physicochemical study of the ternary system phenol - acetic acid - trichloroacetic acid. Zhur. ob. khim. 34 no.9:2823-2826 S '64.

Physicochemical study of the ternary system carbamide - acetamide - trichloroacetic acid. Ibid.:2826-2829

1. Arkhangel'skiy lesotekhnicheskiy institut.

(MIRA 17:11)

· 18(7) AUTHORS:

SOV/20-121-6-17/45 Bokhshteyn, S. Z., Gudkova, T. I., Zhukhovitskiy, A. A.,

kishkin, S. T.

TITLE:

On the Influence of Irreducible Structure Modifications Which Occur During a Plastic Deformation on the Diffusion Mobility (O vliyanii neobratimykh strukturnykh izmeneniy, voznikayushchikh pri plasticheskoy deformatsii, na diffuzionnuyu podvizhnost')

PERIODICAL:

Doklady Akademii nauk SSSR, 1958, Vol 121, Nr 6, pp 1015-1018

(USSR)

ABSTRACT:

This paper investigates the influence of a previous plastic deformation at a high temperature on the diffusion of zink in nickel. This investigation is carried out separately for the volume and for the boundaries of the grains. The previous deformation of the plain samples were carried out by means of expanding tensions $\sigma = 6 \text{ kg/mm}^2$ at a temperature of 700° in the course of 5; 25; 50; and 60 hours. The diffusion currents were determined by autoradiography of an oblique section. The experimental results are given in a table and in a diagram. According to these results, a previous deformation increases considerably the velocity of the diffusion of tin in nickel

Card 1/3

On the Influence of Irreducible Structure Modifications Which Occur During a Plastic Deformation on the Diffusion Mobility

(on the boundary and also in the volume). The volume modification is modified much more than the diffusion on the boundaries. For small deformations, the effect upon the boundaries and upon the grain has the same intensity. According to the analysis of the autoradiograms, the diffusion mainly takes place along the grain boundaries. The influence of the grain boundaries on the diffusion velocity decreases if the previous plastic deformation becomes more intensive. The above-given results may be explained by the following assumption: The plastic deformation at high temperatures causes escential modifications of the microstructure of the alloy. These modifications are irreversible or the initial state may be restored only by a heating of the samples to sufficiently high temperatures. According to an X-ray investigation, the above-discussed previous deformation at high temperatures noticeably diminishes the size of the blocks left after diffusion tempering. The results found for the diffusion of tin in nickel at 800 in the course of 10) hours are given in a table. The irreducible modifications of the structure exercise considerable influence on the diffusion mobility during

Card 2/3

SOV/2c-121-6-17/45 On the Influence of Irreducible Structure Modifications Which Occur During a Plastic Deformation on the Diffusion Mobility

the plastic deformation. A previous plastic deformation intensifies diffusion considerably. There are 3 figures, 2 tables, and 10 references, 6 of which are Soviet.

ASSOCIATION: Vsesoyuznyy nauchno-issledovatel'skiy institut aviatsionnykh

materialov

(All-Union Scientific Research Institute of Aircraft Materials)

PRESENTED: April 19, 1958, by G. V. Kurdyumov, Academician

SUBMITTED: April 1, 1958

Card 3/3

BOKHUA, A.Y.

Some data on the epidemiology of chancroid in Abkhazia. Vest.ven. i derm. 30 no.4:59-60 Jl-Ag 156. (MLRA 9:10)

1. Iz kozhno-venerologicheskoy bol'nitsy Ministerstva zdravookhraneniya Abkhazskoy SSR. (ABKHAZIA--CHANCROID)

BOKHUA, A.V.

Data on the spread of syphilis in Abkhazia before the establishment of Soviet power. Sbor. trud. Med. nauch. ob-vo Abkh. 2:219-223 159. (MIRA 14:10)

1. Iz respublikanskogo kozhno-venerologichenkogo dispansera (glavnyy 1. Iz respublikanianos vrach V.M.Matsaberidze).

(ABKHAZIA_SYPHILIS)

BOKHYAN, S.K., inah.

Self-exciting induction generator with increased frequency and voltage stabilization. Elektrotekhnika 36 ac.2:56-58 F * 65.

(MIRA 18:4)

VOI. 80, 7. [Delia, W.]; PORITANICKA, W. [Politanska, U.];

PORIUSKI, F. [Porawski, E.]; PORITANICKA, I. [Portypaka, A.]

Ferromagnetic phases in the oroducts of nickel ferricyanide thermal decomposition. Zhur.acorg.kmin. 10 ro.12:2693-0697

D. 165. (Min. 1951)

1. Universitet imeni L. Mitskevicha, laboratoriya magnitakhimid, forman', Fol'sha.

BOKIN, M.N., kand. tekhn. nauk.

Rifect of surface smoothness on the selection of substitutes for Rifect of surface structure. Trudy LTMI no.6:380-188 *57. (MIRA 11:5) (Bearing metals)

SOV/137-59-1-1508

Translation from: Referativnyy zhurnal. Metallurgiva: 1959, Nr 1: p 200 (USSR)

AUTHOR: Bokin, M. N.

TITLE: The Effect of Surface Finish on the Endurance Limit of Steel 2Kh13 (Vliyaniye chistoty poverkhnosti na predel vynost vosti stali 2Kh13)

PERIODICAL: Izv. vyssh. uchebn. zavedeniy. Mashinostroveniye. 1958; Nr 1. pp 136-139

ABSTRACT: Investigations were carried out in order to determine how the fatigue strength of a specimen (5) of steel 2Kh.13 subjected to alternating rotary bending while rotating in a Schenk-type fatigue-testing machine is affected by the surface finish produced by various methods of machining. The tests were performed on untempered Ss as well as on S's which had been quenched from a temperature of 1000°C and tempered at 300°; the working surfaces of the S's were subjected to final machining operations consisting of turning (maximum irregularities amounting to 5.8 \mu in height), grinding (1.7 \mu), polishing (0.8 \mu), and superfinishing (0.2 \mu). The endurance limit of

represents an arithmetical mean of three values which were ob-Card 1/2 tained by the following methods. The thermometric (based on the

SOV/137-59-1-1508

The Effect of Surface Finish on the Endurance Limit of Steel 2Kh13

change in temperature), the deformation method (based on the deflection), and the method of the quantity of work absorbed (based on the torque). It is confirmed that machining of metal must be regarded as a process in which not only the shape and the dimensions of a part are changed but its physical properties as well. Machining of a part increases the magnitude of the σ_1 (value of σ_1 increases as the class of finish is increased). Improving the surface finish of important parts made of steel 2Kh13 permitted increasing their loading by 15-20%.

S.G.

Card 2/2

BOKIN, M.N., kand. tekhn. nauk

Photoelectric method for checking kinematic errors in spur gears. Izv.vys.ucheb.zav.; prib. no.3:79-83 '58. (MIRA 12:2)

1. Leningradskiy voyenno-mekhanicheskiy institut.
(Photoelectric measurements) (Gearing, Spor)

BOKIN, M.N., dotsent, kend.tekhn.nauk; TASHNOV, B.D., prof., doktor tekhn.nauk, retsenzent; AL'TFEL'D, G.I., dotsent, retsenzent; YELKIN, V.I., dotsent, retsenzent; OZNOBISHIN, N.V., dotsent, retsenzent; DVCRAKOVSKAYA, A.A., tekhn.rad.

[Fundamentals of interchangeability in the manufacture of machinery; textbook] Osnovy vsaimozameniaemosti v mashinostroenii; uchebnoe posobie. Leningrad, Leningr.voennomekhanicheskii in-t. 1959. 317 p.

(MIRA 14:4)

(Interchangeable mechanisms)

BOKIN, M.N., dotsent, kand.tekhn.nauk

 Leningradskiy voyenno-mekhanicheskiy institut. (Grinding and polishing)

BOKIN,	Control of the Contro
	Using measuring worms in over-all inspection of supr gears with single-profile toothing. Izm.tekh. no.3:1-2 Mr '60. (MIRA 13:6) (Gearing, Spur-Testing) (Measuring worm)

BOKIN, M.N.; YERSHOV, Ye.M.

New brands of epoxy adhesive for sealing glass textolite to metals. Biul.tekh.-ekon.inform.Gos.nauch.-issl.irst.nauch.i tekh.inform. no.9:27-28 '63. (MIRA 16:10)

BOKIN, Mikhail Nikolayevich; BORSHCHEVSKAYA, S.I., red.

[Interchangeability, control, and technical measurements in the manufacture of machinery] Vzaimozameniaemost, kontrol, i tekhnicheskie izmerania v mashinostroenii. Leningrad, Lenizdat, 196%. 255 p. (MIIA 18:7)


BOKIN, M.N.; TSYPIAKOV, O.G. Theory of the impregnation of glass reinforcing fillers with polymer binders. Plast. massy no.2:30-32 66.

(MIRA 19:2)


POKIN, C. T.

37331. Opredelerie plotoosti krepleniya ochistnogo proctranstva zapiski liningr: Gornogo in-ta, T. xxiii, 1949, s. 3-24. Pibliogr: 7 Nazv

SO: Letopis' Zhurnal'nykh Statey, Vol. 7, 1949



BOKIN, P. Ya.					
• •					
Y					
anders de la composition de l		to Maria Material de Arrigador de la companya de l La companya de la co		3	
B. T. R. Vol. 3 No. 4 Apr. 1954 Mechanical Engineering	5155° Modern Require	ments For <u>Grindlig</u> and P. Ia. Bokin. Steklo I Keramik	olishing		
	Describes shortcomings. S produced by national indu	Middelle imbiologiums on i	machines 4		
			7		



BOKIN, P. Ya.

"Physicomechanical Properties of New Polishing Materials." Cand Tech Sci. Inst of Chemistry of Silicates, Acad Sci USSR, Leningrad, 1954. (RZhKhim, No 8, Apr 55)

SO: Sum. No. 704, 2 Nov 55 - Survey of Scientific and Technical Dissertations Defended at USSR Higher Educational Institutions (16)

Bokin, Pola

BARDIN, Anatoliy Nikolayevich; GLEZAROVA, I.L., redak; or; SARKIN, I.G., zasluzhennyy deyatel nauki, professor, redaktor; MEDVEDEV, N.M., kandidat khimicheskikh nauk, redaktor; IVANOV, L.V., inzhener, redaktor; CHURILOVSKIY, V.N., doktor tekhnicheskikh nauk, professor; KAPUSTIVA, T.P., kandidat tekhnicheskikh nauk, dotsent; ROMANOVA, L.V., kandidat tekhnicheskikh nauk, dotsent; BOKIN, P.Ya., inzhener; POLLYAK, V.V., kandidat tekhnicheskikh nauk, redaktor; PANOVA, L.Ya., tekhnicheskiy redaktor.

[Technology of optical glass] Tekhnologiia opt:.cheskogo stekla.

Moskva, Gos. izd-vo lit-ry po stroitel'nym materialam, 1955. 494 p.

(Glass, Optical) (MLRA 9:1)

BOKIN,	P. YA.
USSR/ Chemist	ry - Class
Card 1/1	Pub. 104 - 2/12
Authors :	Bokin, P. Ya.
Title :	The structure of a surface layer of etched glass
Periodical :	Stel. 1 ker. 1, 5 - 8, Jan 1955
Abstract	An investigation was conducted by the <u>Institutes for the Chemistry</u> of <u>Silicates</u> , to determine the influence of various abrasives on the structure of an etched glass surface. Specimens of the vertical-drawn glass and the optical K-8 glass were used for the above purpose. The results obtained are described in detail. Table; graph; illustrations.
Institutions	
Submitted:	

BOKIN. P.Ya.

Calculating the technological process of grinding and polishing plate glass. Stek. i ker. 13 no.8:6-9 Ag '56. (MLRA 9:10)

1. Institut khimii silikatev Akademii nauk SSSR. (Plate glass) (Grinding and pelishing)

Bokin, P. Ya.

USSR/Engineering - Conferences

Card 1/1 Pub. 124 - 29/39

Authors : Bokin, P. Ya., Cand. of Tech. Sc.

Title : Problems of glass grinding and polishing

Periodical : Vest. AN SSSR 26/2, 126-127, Feb 1956

Abstract : Report is submitted on the conference held at the Institute of Chemistry of Silicates of the Acad. of Sc., USSR (Dec. 14-17, 1955) where the subject of glass grinding and polishing was debated.

Institution:

Submitted :

Conference on the grinding and polishing of glass. Stek.i ker. 14 no.6:31-32 Je '57. (MIRA 10:7) (Glass manufacture) (Grinding and polishing)

BOKIN, P. Ya.

AUTHOR:

BOKIN, P.JA., cand, technac.

TITLE:

PA - 2634 The Development of the Theory of Methods for the Grinding and Polishing of Glass. (Razvitye tyeorii protessov shlifovki i

polirovki styckla, Russian)

PERIODICAL:

Vestnik Akademii Nauk SSSR, 1957, Vol 27, Nr 3, pp 129-130

(U.S.S.R.)

Received: 6 / 1957

Reviewed: 7 / 1957

ABSTRACT:

The present paper contains a report on a Conference held in December 1956, which was the fourth coordinating conference in this

The production of plate glass in Russia and in other countries, as well as laboratory work carried out by leading institutes and works laboratories in 1956 was discussed. New data connected with the grinding- and polishing theory, the testing of new grindingand polishing materials, and the latest constructions of grindingand polishing machines were given. It was announced that Soviet scientists are adhering to the physical-chamical theory on the polishing of glass developed by I.V. CREBYEISHCHIKOV and reject the theory of fluidity developed by BILBY (Western method). Moreover, a number of special problems as well as the plan of

operation for 1957 are discussed in short. Among other measures

Card 1/2

PA - 2634

The Development of the Theory of Methods for the Grinding and Polishing of Glass.

to be taken, it is also planned to test a number of new types of machines on a test stand which is to be erected especially for this purpose in a plant belonging to the Ministry of Industry. It was suggested that the laboratories of backward plants and factories be improved and extended.

ASSOCIATION:

Not given

PRESENTED BY:

SUBMITTED:

AVAILABLE:

Library of Congress

Card 2/2

KACHALOV, N.N.; BOKIN, P.Ya.; KORELOVA, A.I.

Glass grinding and polishing with an apparatus of great pressure and speed. Trudy LTI no.49:18-24 *58. (MIRA 15:5) (Glass) (Grinding and polishing)

KACHALOV, N.N.; BOKIN, P.Ya.; DEMICHEV, S.A.; ROMANOV, B.Ye.

Grinding glass with garnet powder. Trudy ITI no.49:25-29

'58.

(Glass) (Grinding and polishing) (Garnet)

New polishing materials. Trudy LTI no.49:30-36 '58. (MIRA 15:5) (Glass)
(Grinding and polishing)

BOKIN, P.Ya.

Relation of thickness of the relief effect and the removed layers in polished glass to abrasive grain sizes. Stok. 1 ker. 15 no.42 8-10 Ap '58. (MIRA 11:5)

1. Institut khimii silikatov AN SSSR.
(Grinding and polishing) (Glass manufacture)

BOXIN PYA

Z/012/60/000/02/019/019 E073/E435

AUTHOR:

None given

TITLE:

Second Conference on Grinding and Polishing of Glass

PERIODICAL: Silikaty, 1960, Nr 2, p 213

ABSTRACT:

This conference was held in Jablonec n. Nisou on September 22-25, 1959. Among the 150 participants were Dr A.F.Fedoseyev, Professor, Vice-President of the Institute for Silicate Chemistry of the Soviet Academy of

Sciences, P. Ya. Bokin, Candidate of Technical Sciences
(USSR) and Dr A. Kaller (Jena, East Germany). 19 Papers
were read: P. Ya. Bokin (USSR) read a paper on the
development of the theory of glass grinding in the USSR;
A. Kaller read a paper on the relation between some
physical properties of iron oxides and their polishing
effects; J. Korelova read a paper on the development of
the theory of glass polishing; A.S. Totes (USSR) read a
paper on intensifying the process of glass polishing;
S. MinaY (Prerov) read a paper on the importance of
physical and chemical factors during polishing of silicate
glass which was the most valuable Czech contribution on
theoretical research; J. Voldan read a paper on the effect

Card 1/2

Z/012/60/000/02/019/019 E073/E435

Second Conference on Grinding and Polishing of Glass

of recrystallization on the resistance to grinding of molten rocks and basic glasses. Short contributions included the following; J.Lederer dealt with expressing of polished surfaces. F.Zacek dealt with granulometric analysis and making such analysis more accurate. J. Götz dealt with the effectiveness in polishing of iron oxides as a function of the annealing temperature. I. Solc dealt with the stability of polished surfaces. The following five Czechoslovak research establishments participated in the conference; levellery, Jablonec n. Nisou; 2) Research Institute for Optics and Precision Mechanics, Prerov; 3) Research Establishment for flat glass, Teplice; 4) Glass Research Institute, Hradec Kralove; 5) Minerals Research

Card 2/2

Conference on glass grinding and polishing. Stak.i ker. 17 no.4:46-47 Ap *60. (MIRA 13:8) (Glass manufacture-Congresses)

BOKIN, P.Ya.

Fracture of the surface layer of glass by muans of microindentors. Inzh.-fiz. zhur. 4 no.4:126-128 Ap '61. (MIRA 14:5)

1. Institut khimii silikatov AN SSSR, g. Leningrad. (Glass-Testing)

Strength of grains of abrasive powders. Stel. i ker. 18 no.7:
9-12 J1 '61. (MIRA 14:7)

(Glass manufacture) (Abrasives)

S/072/62/000/009/002/002 B117/B136

AUTHOR:

Bokin, P. Ya.

TITLE:

Symposium on "Mechanical Properties and Structure of In-

organic Classes"

PERIODICAL: Steklo i keramika, no. 9, 1962, 45 - 46

TEXT: The symposium, held in Leningrad in April, 1952, was organized by Leningradskoye pravleniye Vsesoyuznogo khimicheskogo obshchestva im. D. I. Mendeleyeva (Leningrad Board of Administration of the All-Union Chemical Society imeni D. I. Mendeleyev), Institut khimii silikatov im. I. V. Grebenshchikova AN SSSR (Institute of Silicate Chemistry imeni I. V. Grebenshchikov AS USSR), Gosudarstvennyy opticheskiy institut im. S. I. Vavilova (State Optical Institute imeni S. I. Vavilov), and Gosudarstvennyy nauchno-issledovatel'skiy institut stekla (State Scientific Research Institute of Glass). It was attended by 200 delegates from scientific research institutes and industrial establishments. Following are the most interesting of the 20 reports: G. M. Bartenev, A. S. Yeremeyeva, and V. A. Kargin reported on variations in the mechanical properties of glass in the field of polymorphous conversions including a third (mechanical-Card 1/4

S/072/62/000/009/002/002 B117/B136

Symposium on "Mechanical ...

•

chemical) type of depolymerization discovered by the authors. V. V. Tarasov, V. A. Ratobyl'skaya reported results of experimental studies on sodium borate glasses, emphasizing the polymer structure of these glasses. A. V. Gladkov, Ye. A. Karabutova, and Ye. A. Yunitskiy reported on investigations of lead silicate and lead borate glasses which support the theory that these glasses are of polymer structure. G. M. Bartenev and A. S. Yeremeyeva spoke about the residual stresses in inorganic single-phase glasses, glass formers, and hyperelastic stresses in microheterogeneous glasses. O. K. Botvinkin and N. I. Ananich reported on three types of in glass which result from its rapid quenching, the development of anisotropic structures in its elements, the composition and form of its microphases; obviously these stresses affect its mechanical properties. K. T. Bondarev and V. A. Minakov spoke of relations between variations in strength and heat treatment of lithium aluminosilicate glasses containing small amounts of silver and of sodium-calcium aluminate glasses, with fluorino used as a catalyst. V. G. Chistoserdov's and I. A. Soboleva's report dealt with the bending strength of photosensitive lithium and cordierite type crystalline glasses at different temperatures. A. I. Avgustinik and L. S. Klanina reported on the relationship between the microhardness of lithium calcium silicate glasses and the development of Card 2/4

S/072/62/000/009/002/002 B117/B186

Symposium on "Mechanical ...

"pre-seeding" groups and crystals determined in these by IR-spectroscopy. A. I. Korelova, O. S. Alekseyeva, and M. G. Degen spoke about the influence of the lithium oxide content and heat treatment on the microhardness and brittleness of lithium silicate glasses. F. K. Aleynikov, V. A. Slizhis, R. P. Paulavichyus, and P. V. Dundzis reported on an investigation of the microhardness, microtensile strength, constants of elasticity, and structure of binary and ternary glasses containing various monovalent and bivalent metals, as well as on some commercial glasses. K. T. Bondarev, and S. Ye. Dvorkina spoke about the effect of the temperature of heat treatment on the mechanical strength of sodium borosilicate glasses. S. M. Brekhovskikh, G. K. Demishev, and L. N. Butovich stated that the constants of elasticity, the dielectric constant, and the loss angle tangent of perpendicularly drawn window glass all increase with increasing gamma dose. Ye. S. Sorkin described the method of investigating the crystallization in aluminosilicate glasses containing titanium oxide by measuring the deformation under isothermal static compression. F. F. 'Vitman, I. A. Boguslavskiy, and V. P. Pukh stated that they had succeeded in increasing the strength of flat glass by nearly 10 vimes (up to 100 kg per mm²) by thermal hardening in a liquid and subsequen; etching in hydrofluoric acid. F. F. Vitman and V. P. Pukh reported on tensile and bending tests of Card 3/4

Symposium on "Mechanical ...

S/072/62/000/009/002/002 B117/B186

glass threads depending on the composition of the glass. G. M. Bartenev and L. I. Motorina found that the strength of glass fibers subjected to tensile stress can be improved by heat treatment. The delegates recommended to intensify research work on the relationship between the mechanical properties and the structure of inorganic glasses.

Card 4/4

KORELOVA, A. I. and BOKIN, P. Ya.

"Mechanical properties and microstructure of crystallized glasses."

(Institute of Silicate Chemistry)

At the Division of Physical Chemistry and Technology of Inorganic Materials, Acad. 101.

USSR, a scientific council on the problem of sitalls has been established. The Council is accordinating hody for busic scientific research on sitalls, glass, fiber glass, stoneware, refractory and superrofractory materials, and coatings. The purpose of the Council is primarily to contribute to the improvement of the strength and impact resistance of existing materials. In 1963, the council held two sessions.

(Steklo i keramika, no. 6, 1964, 48-49)

ALEKSEYEVA, O. S.; BOKIN, P. Ya.; GOVOROVA, R. A.; KORELOVA, A. I.; NIKANDROVA, G. A.

4

"Structural variations in lithium silicate and lithium alumosilicate glasses in the process of crystallization and their effect on mechanical properties."

report submitted for 4th All-Union Conf on Structure of Glass, Leningrad, 16-21 Mar 64.

L 00478-66 EWP(e)/EWT(m)/EWP(1)/EWP(b) GS/WH ACCESSION NR: AT5013393 UR/0000/65/000/000/0143/0149 TITIE: Resistance to surface grinding and mechanical properties of certain glasses and glass-crystalline materials SOURCE: AN SSSR. Institut khimii silikatov. Strukturnyye prevrashcheniya v steklakh pri povyshennykh temperaturakh (Structural transformations in glass at high temperatures). Moscow, Izd-vo Nauka, 1965, 143-149 TOPIC TAGS: glass surface strength, glass property, glass grinding, optical ABSTRACT: The method of mutual grinding was used to study the strength characteristics of K8, BK6, F2, and TF4 optical glasses and of glass-crystalline materials prepared from these glasses. Quartz glass (H =710 kg/mm²) and a powder of silicon carbide (H = 2900 kg/mm²) were taken as the standards. The influence of the relative size of the glasses being ground on the value of the surface strength Po obtained was determined. It was found that in order to determine Po of the optical glasses within 8 - 10%, the surface areas of the samples used in the mutual grinding should differ from each other by a factor of no more Card 1/2

the detection of internal changes in the structure of lithium silicate glasses caused by a variable content of lithium oxide. The relationship between the surface strength of glasses and glass crystalline materials and their microhardness and Young's modulus was elucidated. "Measurements of the hardness of glasses and glass-crystalline materials were carried out by G. A. Nikandrova." Orig. art. has: 3 figures and 4 tables. ASSOCIATION: none SURMITTED: 21Dec64 RNCL: 00 SUB CODE: MT	crystalline materials wit of the mutual grinding me that the method is fully	ngth of the ground sample is 3 to 5 times less than that Grinding of glasses with a strength of 0.18 and glass- th a strength of 4.6 showed that the general principle ethod was closely obeyed for all the samples, and hence	
SUBMITTED: 21Dec64 ENCL: 00 SUB CODE: MT	the detection of internal caused by a variable cont	l changes in the structure of lithium silicate glasses	ti
·····································	nardness and Young's modu glasses and glass-crystal	ilus was elucidated. "Measurements of the hardness of	
	hardness and Young's modu glasses and glass-crystal Orig. art. has: 3 figure	ilus was elucidated. "Measurements of the hardness of	
O REF SOV: 004 OTHER! 000	hardness and Young's modu glasses and glass-crystal Drig. art. has: 3 figure ASSOCIATION: none	ilus was elucidated. "Measuriments of the hardness of lline materials were carried out by G. A. Nikandrova." as and 4 tables.	

00477-66 EWP(e)/EWT(m)/EWP(1)/EWP(b) ACCESSION NR: AT5013394 UR/000D/65/000/000/0149/0157 AUTHOR: Bokin, Korelova, A. I.; Govorova, R. A.; Nikandrova, G. A. 44 TITIE: Mechanical properties and microstructure of lithium silicate glasses at various stages of crystallization 6,44 SOURCE: AN SSSR. Institut khimii silikatov. Strukturnyye prevrashcheniya v steklakh pri povyshennykh temperaturakh (Structural transformations in glass at high temperatures). Moscow, Izd-vo Nauka, 1965, 149-157 TOPIC TAGS: glass mechanical property, glass crystallization, lithium silicate glass, glass structure ABSTRACT: Certain mechanical properties and their dependence on the microstructure of initial and crystallized lithium silicate glasses containing 23.4 and 34.4 mole % lithium oxide were investigated. The glasses were subjected to various thermal treatments, and their microstructure was studied. The change in the size and quantity of spherulites and in the density, micronardness, elastic constants, and surface strength of the glasses was studied as a function of the conditions of thermal treatment. This combined study of the microstructure and mechanical properties of lithium silicate glasses reveals that changes in

L 00477-66					
ACCESSION HR:	AT5013394				
Buch properties				.	
conditions are	closely place d	uring the cryste	lligation of ore	sses under various	
turn depends on	the composition	to changes in (illisation of gla heir microstruct of the separati	ure. which in	
Orig. art. has:	7 figures and	2 tables	of the separati	of crystals	
ASSOCIATION: DO					
	The state of the s	沙沙湖沿湖 城			
SUPPLITED: 21De	c64	ENCL: 00			
NO REP SOVE OOS			SUB COL	E: MT	
		COHER! 000			
	THE TAXABLE				
					12 (A)
					30
				3.3.15111111111111111111111111111111111	池
					1100 A
Card 2/2					
社会特别是中国的全部支持的	in programme and				
ALL WILLIAM TO THE TANK OF THE PARTY OF THE	Out of the Late of	TANK BUTTON STATE	型型等等 医皮肤病		1.12

L 00476-66 EWP(6)/EWT(m)/EWP(1) - CS/WH ACCESSION NR: AT5013395 UR/0000/65/000/000/0158/0176 P. Ya. Korelova, AUTHOR: Bokin, Alekseyeva, O. S.; Nikandrova, G. A. TITIE: Relationship between certain mechanical propurties and the microstructure of crystallized lithium aluminosilicate glasses 1544 SOURCE: AN SSSR. Institut khimii silikatov. Strukturnyye prevrashcheniya v steklakh pri povyshennykh temperaturakh (Structural transformations in glass at high temperatures). Moscow, Izd-vo Nauka, 1965, 158-176 TOPIC TAGS: glass crystallization, glass mechanical property, lithium metasilicate, lithium aluminosilicate ABSTRACT: A series of mechanical properties (density, hardness, elastic constants, and surface strength) were studied as a function of the microstructure of lithium aluminosilicate glass subjected to crystal lization funder various

conditions of thermal treatment. The microstructure was investigated by optical and electron microscopy; x-ray phase analysis was also employed. In samples subjected to thermal treatment at 530-700C, the increase in density is due to the crystallization of lithium metasilicate, which is also responsible for the

L-00476-66-

ACCESSION NR: AT5013395

increase in microhardness, Young's modulus, and surface strength. A still greater increase in density at 740C and above, associated with a decline in mechanical properties, is caused by the formation of a \$\beta\$-eucryptite solid solution, which is much more brittle than glass. It is concluded that the methods selected for studying the mechanical properties are sufficiently sensitive and adequately reflect changes in the process of crystallization and in the nature of the crystallizing phases caused by different conditions of thermal treatment. The results showed that the appearance of any crystalline phase in the glass is associated with the formation of a microstructure characteristic of this phase, and this in turn is manifested by changes in the curves representing the mechanical properties versus the temperature of the thermal treatment. Orig. art. has: 13 figures and 2 tables.

ASSOCIATION: none

SUMMITTED: 21Dec64

SUB CODE:

NO REF SOVI. 013